

8-Channel DigitalMedia 8G™ Single-Mode Fiber Input Blade for DM® Switchers

- > Modular input blade for a DM-MD64X64 or DM-MD128X128 switcher
- > Provides eight independent DM 8G® Single-Mode Fiber inputs
- > Supports cable lengths up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber^[1]
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Occupies a single output blade slot

The DMB-I-S2 is an input blade designed for use with any blade-based Crestron® DigitalMedia™ Switcher. It provides eight independent DM 8G® SM Fiber inputs. Each DM 8G SM Fiber input enables the connection of a DM 8G SM Fiber Transmitter, or the output of another DM® switcher. Just one single-mode fiber optic strand is required per input, supporting distances up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber optic cable.^[1]

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

SPECIFICATIONS

Video

Input Signal Type: DM 8G® SM Fiber (DigitalMedia™ over one single-mode fiber optic strand)^[1]

Formats: DM 8G SM Fiber w/Deep Color & 3D, HDCP content protection support

Input Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Audio

Input Signal Type: DM 8G SM Fiber



Formats: Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

Communications

DigitalMedia: DM 8G SM Fiber, HDCP, EDID, CEC, Ethernet

Connectors

INPUT SMF/LC 1 – 8: (8) LC female optical fiber connectors; DM 8G Single-Mode Fiber inputs; Each connects to the DM 8G SM Fiber output of a DM transmitter or other DM device via CRESFIBER8G-SM single-mode fiber optic cable^[1]

Indicators

ACT: (1) green LED, indicates blade activity
MSG: (1) red LED, indicates an error message has been generated
INPUT SMF/LC: (8) green LEDs, indicate DM link status for each corresponding input

Construction

Plug-in blade, occupies (1) DM Switcher input blade slot, includes metal faceplate w/black finish

Weight

1.6 lb (726 g)

MODELS & ACCESSORIES

Available Models

DMB-I-S2: 8-Channel DigitalMedia 8G™ Single-Mode Fiber Input Blade for DM® Switchers

Available Accessories

CRESFIBER8G-SM-P: CresFiber® 8G Single-Mode Fiber Optic Cable, plenum

CRESFIBER8G-SM-CONN-LC-12: CresFiber® 8G Single-Mode Fiber Optic Cable Connector, LC, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit (AFL Telecommunications™)

Notes:

1. The maximum cable length for DigitalMedia 8G Single-Mode Fiber (DM 8G SM Fiber) is 7.5 miles (12 km) using Crestron [CRESFIBER8G-SM](#) or third-party G.652.D (or better) single-mode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, CresFiber, DigitalMedia, DigitalMedia 8G, DM, and DM 8G are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.