

16-Channel Analog Audio Breakout Box

- > Enables analog audio connectivity for up to two HDMI® input/output blades
- > Compatible with DMB-4K-I-HD input blades and DMB-4K-O-HD output blades
- > Provides eight stereo audio inputs per input blade
- > Provides eight stereo audio outputs per output blade
- > Handles balanced or unbalanced audio signals
- > Single-space 19" rack-mountable



The AUD-BOB-1602 is a 1RU rack-mountable breakout box designed for use with up to two **DMB-4K-I-HD** input blades, or up to two **DMB-4K-O-HD** output blades, or one of each. It facilitates the connection of analog audio signals to each blade via detachable terminal blocks, providing eight balanced stereo inputs per input blade, and/or eight balanced stereo outputs per output blade.

The connection to each blade is made using the included VHDCI interconnect cables. The AUD-BOB-1602 is available with a choice of 8 ft (2.44 m) or 20 ft (6.1 m) interconnect cables. The interconnect cables are also available for purchase separately to accommodate applications requiring two different lengths.

SPECIFICATIONS

Audio

Input/Output Signal Type: Analog stereo

Format: Stereo 2-channel

Connectors

A1 – A8, B1 – B8: (32) 3-pin 3.5mm detachable terminal blocks comprising (16) balanced/unbalanced stereo line-level analog audio inputs or outputs^[1]

ANALOG AUDIO I/O A – B: (2) 68-pin VHDCI female Each connects to one input blade or output blade using a CBL-VHDCI interconnect cable (Qty. 2 included)

G: (1) 6-32 screw, chassis ground lug

Power Requirements

This is a passive product that requires no power for operation

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 0 BTU/hr

Enclosure

Chassis: Metal, black finish, vented sides

Front Panel: Metal, black finish with polycarbonate label overlay

Mounting: Freestanding or 1RU 19-inch rack-mountable with front or rear panel facing out (adhesive feet and rack ears included)

Dimensions

Height: 1.70 in (44 mm)

Width: 17.28 in (439 mm); 19.0 in (483 mm) with rack ears

Depth: 6.63 in (169 mm)

Weight

3.5 lb (1.6 kg)

MODELS & ACCESSORIES

Available Models

AUD-BOB-1602-CBL8_PAK: 16-Channel Analog Audio Breakout Box w/8 ft Interconnect Cables

AUD-BOB-1602-CBL20_PAK: 16-Channel Analog Audio Breakout Box w/20 ft Interconnect Cables

Included Accessories

CBL-VHDCI-8: VHDCI Interconnect Cable for AUD-BOB-1602, 8 ft (Qty. 2 included with AUD-BOB-1602-CBL8_PAK)

CBL-VHDCI-20: VHDCI Interconnect Cable for AUD-BOB-1602, 20 ft (Qty. 2 included with AUD-BOB-1602-CBL20_PAK)

Available Accessories

CBL-VHDCI-8: VHDCI Interconnect Cable for AUD-BOB-1602, 8 ft

CBL-VHDCI-20: VHDCI Interconnect Cable for AUD-BOB-1602, 20 ft

Notes:

1. Refer to the connected blade(s) for I/O specifications.

AUD-BOB-1602 16-Channel Analog Audio Breakout Box

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.
©2015 Crestron Electronics, Inc.



AUD-BOB-1602 – Rear view

