Crestron RL2

Sound Bar for Crestron RL® 2

- > High-quality, full-range amplified stereo sound bar
- > Designed for use with the Crestron RL® 2 Group Collaboration System
- > Delivers enhanced sound quality and performance for use with any flat panel display
- > Mounts to a wall or sits on a shelf
- > Unbalanced stereo line-level audio input^[1]
- > 100 to 240 Volt AC powered

The CCS-SPK-SB-100 is a stereo sound bar designed to provide enhanced audio performance for a flat panel display. Its full-range, front-firing speakers offer a dramatic improvement over the small, rear-facing speakers typical of many display devices. Brackets included with the sound bar allow for attachment to a wall surface or placement on a shelf below or above the display. Built-in amplification allows for direct connection to the line-level audio output of the display device, or to the output of a separate audio preamp, switcher, mixer, tv tuner, or codec. [1]

The CCS-SPK-SB-100 sound bar is ideally suited for use with the Crestron RL® 2 Group Collaboration System and other unified communication and videoconferencing systems. It is equally well-suited for use in any small to medium sized room or public space in a hotel, restaurant, museum, medical center, airport, office building, or residence.

SPECIFICATIONS

Features & Performance

Woofers: (2) 3 inch (76 mm) ported Tweeters: (2) 1 inch (25 mm) dome

Amplifier Power: 25 Watts per channel, stereo Frequency Response: 70 Hz to 20 kHz (±3 dB)

Maximum SPL: 85 dB @ 1W/1m

Input Sensitivity: 1 Vrms for rated output

Connections

AUDIO IN, L/R: (2) RCA female;

Unbalanced stereo line-level audio input [1]:

Maximum Input Level: 2 Vrms; Input Impedance: 10k Ohms

100-240V~50/60Hz: (1) Attached 6 ft (~2 m) power cord

Controls

POWER: (1) Rocker switch, turns main power on or off

Power Requirements

Main Power: 0.3 Amps maximum @ 100-240 Volts AC, 50/60 Hz

Environmental

Temperature: 41° to 104° F (5° to 40° C) Humidity: 10% to 90% RH (non-condensing)

Construction

Enclosure: Plastic housing with cloth covered grille

Mounting: Freestanding or wall mount (brackets included)

Dimensions

Height: 3.50 in (89 mm);

3.90 in (99 mm) with shelf placement brackets

Width: 39.00 in (991 mm) **Depth:** 3.19 in (81 mm);

3.40 in (87 mm) with wall mount brackets

Weight

10.0 lb (4.6 kg)

MODELS & ACCESSORIES

Available Models

CCS-SPK-SB-100-B: Sound Bar for Crestron RL® 2, Black



CCS-SPK-SB-100-B - With Grille Removed



CCS-SPK-SB-100 Sound Bar for Crestron RL® 2

Available Accessories

CBL Series: Crestron® Certified Interface Cables

Notes:

1. The CCS-SPK-SB-100 has a fixed input level. It must be connected to an audio source equipped with adjustable audio output level.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Crestron RL are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2016 Crestron Electronics, Inc.



Rear Panel

