B12-2YR

Domotz™ Remote Network Management Agent Plus 24 Months of Residential Service



- Remote monitoring and management of any type and number of devices
- Network devices are automatically discovered and identified
- Monitors a variety of device attributes and events, such as temperature, speed, consumable status, etc.
- On-demand and scheduled speed tests and bandwidth analysis to detect possible bottlenecks or packet loss.
- SNMP and TCP service monitoring can create an alert if a device exceeds a certain temperature, or a printer's toner cartridge drops below a certain level
- Wi-Fi® Access Point monitoring
- External IP Host monitoring
- Device response time monitoring and statistics
- Managed network switch port mapping with port status, upload/download traffic, lost packets, and errors, with historical graphs
- Advanced network data and reporting

The B12 Domotz™ Box is an all-in-one remote network monitoring and management agent that allows integrators, MSPs, and IT professionals to easily detect and troubleshoot network and device problems in real time. Gain full control over a network through this powerful system that detects and monitors all IP devices. Remotely access connected devices, manage device power, perform network diagnostics, and be alerted in real time about network and device issues.

The B12 improves client care with proactive issue detection and prevention, increasing service revenue while reducing on-site service calls. It provides access to all network and device data from a single convenient dashboard with instant syncing across devices and custom push notifications via mobile, desktop, or partner integrations.

Specifications

Memory & Storage

RAM 1 GB DDR3L Storage 4 GB eMMC

Connectors

(1) Gigabit Ethernet port

(1) USB 2.0 port (for future releases)

(1) Micro USB port for power

Indicator

(1) LED

Control

Factory reset button

Power Supply

Input 100-240 VAC, 50-60 Hz, 0.5 A

Output 5 VDC, 2 A

Consumption 10 W maximum

Environmental

Temperature 32° to 104° F (0° to 40° C) **Humidity** 80% RH (non-condensing)

Dimensions

 Height
 1.63 in. (42 mm)

 Width
 4.25 in. (108 mm)

 Depth
 2.81 in. (72 mm)

Weight

4.4 oz (125 g)

Compliance

FCC Part 15 Class B digital device, IC Class B, CE

Models

B12

Domotz™ Remote Netork Management Agent

B12-1YR

 $\mathsf{Domotz}^\mathsf{TM}$ Remote Netork Management Agent Plus 12 Months of Residential Service



B12-2YR

Domotz™ Remote Network Management Agent Plus 24 Months of Residential Service

B12-2YR

Domotz™ Remote Netork Management Agent Plus 24 Months of Residential Service

B12-5YR

Domotz™ Remote Netork Management Agent Plus 60 Months of Residential Service

Included Accessories

Power supply (100/120V)

Flat CAT 5e cable

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Domotz is either a trademark or registered trademark of Domotz Ltd. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2021 Crestron Electronics, Inc.

Rev 05/17/21



