

Panasonic		WV-SW355	
Description		Dome Camera	
Number of documented streams:	2	Documented Simultaneous Streams:	Not documented

TSX

MJPEG

Supported:	Yes		
Resolution:	640x480 VGA	Camera Quality Setting:	Standard
Frames per second (fps):	5	Switching Time:	1~2
URL with user name and password:			
http://<username>:<password>@<IP address>:80/cgi-bin/camera?Resolution=640x480&Quality=Standard			
URL without username and password			
http://<IP address>/nphMotionJpeg?Resolution=640x480&Quality=Motion			
URL Example			
http://172.30.87.145/nphMotionJpeg?Resolution=640x480&Quality=Motion			

H.264

Supported	Yes		
Resolution:	640x480 VGA	Max Bandwidth	1 Mb/s Select Transmission priority to Constant bit rate
Frames per second (fps):	N/A	Switching Time	1~5
I-Frame Setting	Refresh interval to 0.5s		
URL with user name password:			
rtsp://<username>:<password>@<IP address>/MediaInput/h264			
URL without user name password:			
rtsp://<IP address>/MediaInput/h264			
URL Multicast:			
-			
URL Example			
rtsp://admin:admin@192.168.1.114/MediaInput/h264			

TPMC-V12/15, DGE-2. TPMC-8X-GA**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Good
Frames per second (fps):	5	Switching Time:	1-2 secs
URL with user name and password:			
http://<username>:<password>@<IP address>:<port>/nphMotionJpeg?Resolution=1280x720&Quality=Low			
URL without username and password			
N/A			
URL Example			
http://172.30.176.143:80/nphMotionJpeg?Resolution=1280x720&FPS=15&Quality=Low			

H.264

Supported	Yes		
Resolution:	1280x720	Max Bandwidth	Constant bit rate
Frames per second (fps):	30	Switching Time	1-2 secs
I-Frame Setting	.5		
URL with user name password:			
rtsp://<user>:<password>@<IP address>:<port>/MediaInput/h264			
URL without user name password:			
rtsp://<IP address>:554/MediaInput/h264			
URL Multicast:			
N/A			
URL Example			
rsp://admin:12345@172.30.176.143:554/MediaInput/h264			

TPMC-4SM**MJPEG**

Supported:	Slow switching		
Resolution:	640x480 VGA	Camera Quality Setting:	Standard
Frames per second (fps):	5	Switching Time:	5~7
URL with user name and password:			
http://<username>:<password>@<IP address>:80/cgi-bin/camera?Resolution=640x480&Quality=Standard			
URL without username and password			
-			
URL Example			
-			

H.264

Supported	Some Pixelation		
Resolution:	320x240 QVGA	Max Bandwidth	512Kbps - Select Transmission priority to Constant bit rate
Frames per second (fps):	N/A	Switching Time	1~8
I-Frame Setting	Refresh interval: 0.5s		
URL with user name password:			
rtsp://<username>:<password>@<IP address>/MediaInput/mpeg4			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			

Crestron App**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Low
Frames per second (fps):	30	Switching Time:	2-4sec
URL with user name and password:			
http://<username>:<password><IP Address>:80/nphMotionJpeg?Resolution=1280x720&Quality=Low			
URL without username and password			
http://<username>:<password><IP Address>:80/nphMotionJpeg?Resolution=1280x720&Quality=Low			
URL Example			
http://admin:12345@172.30.177.43:80/nphMotionJpeg?Resolution=1280x720&Quality=Low			

H.264

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			