

NOTES:

"CRESNET" CABLE:
(1) PAIR #18AWG,
(1) TWISTED PAIR 22AWG
WSHIELD (BY E.C.)
NON-PLENUM PN: CRESNET-NP-TL
PLENUM PN: CRESNET-P-TL

RS-232 CABLE:
(1) TWISTED PAIR 22AWG
(1) SHIELD
DB-9 CONNECTOR (BY E.C.)

CABLE:
(1) TWISTED PAIR 18AWG
(1) SHIELD
(BY E.C.)

CABLE:
CAT5E ETHERNET

***ALL PHYSICAL DEVICE LOCATIONS TO BE COORDINATED WITH ARCHITECT.

CRESNET WIRING RUNS SHOWN AS HOME RUN TO EACH DEVICE FOR OPTIMAL PERFORMANCE. DAISY CHAIN AND OR STAR TOPOLOGIES ARE PERMITTED TO SUIT INSTALLATION NEEDS. TOTAL END TO END WIRE LENGTH NOT TO EXCEED 500'.

PROJECT: 120V 42-CKT SWITCHING SYSTEM DATE BY 00 12-03-08 VB				PO #:					
DBO IECT: 120V 42	10000 42	- NOTH VOC	FOCATOR.	L	QUOTE #:	SAI ES BED.		DISTRIBITOR:	
				7647		3/6	011		

15 Volvo Drive Rockleigh NJ 07 Tel: 888-273-78' Fax: 201-767-60

TITLE:

ONE-LINE RISER (FOR INFORMATION ÒNLY)

DRAWING:

1.0