CSM-QMTDC-DRP-3-CN

Digital QMT® Drapery Motor for CSS-DRAPERY, Cresnet®

- > For Crestron® Drapery Systems with tracks up to 240 inches (6096 mm)^[1]
- > Long-life brushless motor featuring Digital Quiet Motor Technology™ for nearly imperceptible operation
- > Built-in Cresnet® wired communications
- > Fully integrated design, with no external modules required
- > 24 Volt low-voltage power
- > Real-time activity monitoring and status feedback
- > Touch Motion feature allows users to activate motor by simply pulling on drapery fabric
- > Local pushbutton interface for testing
- > Local diagnostic LEDs to indicate drapery system status
- > Smooth starts and stops with adjustable limits
- > Protective features that detect and react to obstructions in the drapery path to avoid motor or fabric damage
- > Limited Lifetime Warranty

NOTE: The CSM-QMTDC-DRP-3-CN is only available as part of a Crestron® drapery system and cannot be ordered on its own. To configure drapery systems or order drapery system parts and accessories, please use the Crestron Design Tool for Crestron Shading Solutions or call 1-855-53-S-H-A-D-E (537-4233) for support.

Featuring Digital Quiet Motor Technology™, the CSM-QMTDC-DRP-3-CN motor provides quiet yet robust operation for Crestron® Drapery Systems with tracks up to 240 inches (6096 mm). [1] Fully integrated electronics eliminate the need for bulky add-on interface modules, allowing for an easy, streamlined installation. The CSM-QMTDC-DRP-3-CN uses the dependable Cresnet® wired network for communications. An infiNET EX® wireless version of the motor is also available (model CSM-QMTDC-DRP-3-EX).

The CSM-QMTDC-DRP-3-CN can integrate seamlessly into a Crestron control system to be operated from keypads, wireless remotes, and touch screens. For easy setup, a local three-button interface on the motor lets users test the drapery system after installation and set drapery limits. Power is supplied to the CSM-QMTDC-DRP-3-CN via dedicated Crestron power supplies, such as the CSA-PWS40 or CSA-PWS10S-HUB. The CSA-PWS10S-HUB is capable of distributing power to up to ten drapery motors from one unit.

Quiet Motor Technology

The drapery motor utilizes the quiet, precision-controlled Quiet Motor Technology to control the movement of the draperies, keep track of the drapery's position, and adjust the drapery to the user's desired preset positions.

Touch Motion Feature

By gently pulling on the edge of the drapery fabric, users can activate the CSM-QMTDC-DRP-3-CN to move the draperies along the track to an open or closed position. In the event of a power outage, a manual override feature allows users to manually move the draperies.



Cresnet

The drapery motor uses the dependable Cresnet wired network for communication between devices. The Cresnet bus offers easy wiring and configuration, carrying bidirectional communication and 24VDC power to each device over a simple 4-conductor cable.

SPECIFICATIONS

Motor Specifications

Torque: 1.62 Nm

Motor Speed: 10-50 rpm

Duty Cycle: 15 min on/15 min off at 1.62 Nm

Maximum Track Length Supported: 240 in (6096 mm)[1]

Power Requirements

Cresnet® Power Usage: 42.5 Watts (1.77 Amps at 24 Volts DC); Requires a CSA-PWS Series power supply, see Available Accessories for model numbers

Communications

Cresnet

Connectors

NET: (1) 2-conductor pigtail with inline detachable terminal block

Controls & Indicators

LED: (1) Multicolor LED, indicates motor status

Buttons: (3) Pushbuttons (Close, Configure, Open), allows for testing and setting up drapery system



CSM-QMTDC-DRP-3-CN

Digital QMT® Drapery Motor for CSS-DRAPERY, Cresnet®

Environmental

Temperature: 32° to 104° F (0° to 40° C) Humidity: 10% to 90% RH (non-condensing)

Dimensions

Height: 9.10 in (231 mm) Width: 2.60 in (66 mm) Depth: 3.00 in (76 mm)

Weight (Without Cables)

1.6 lbs (0.73 kg)

MODELS & ACCESSORIES

Available Models

CSM-QMTDC-DRP-3-CN: Digital QMT® Drapery Motor for CSS-DRAPERY,

CSM-QMTDC-DRP-3-EX: Digital QMT® Drapery Motor for CSS-DRAPERY, infiNET EX®

Available Accessories

CSA-PWS40: Power Pack for Crestron® Shade Interfaces & Motors CSA-PWS10S-HUB: 10-Motor Power Supply and Cresnet® Hub CSA-PWS10S-HUB-CAEN-1X1: 10-Motor Power Supply and Cresnet® Hub w/ CAEN 1X1 Enclosure

Notes:

1. Actual maximum track length supported is dependent on drapery fabric chosen. All drapery fabric is customer supplied.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, visit www.crestron.com/opensource.

Crestron, the Crestron logo, Cresnet, infiNET EX, QMT, and Quiet Motor Technology are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. @2016 Crestron Electronics, Inc.