

# DigitalMedia™ Fiber Transmitter 100

- > DigitalMedia™ Fiber transmitter and HDMI® interface
- > DM® Fiber output supports up to 1000 ft (300 m) cable length<sup>[1]</sup>
- > Provides a single HDMI digital video/audio input
- > Also supports DVI and DisplayPort Multimode sources<sup>[2]</sup>
- > Handles HD video with Deep Color, 3D, and HDCP
- > Handles Dolby® TrueHD, DTS-HD Master Audio™, and uncompressed 7.1 linear PCM audio
- > Includes USB HID device port for connection to a computer
- > Provides a 10/100 Ethernet connection
- > Enables device control via CEC, IR, and Ethernet
- > Allows quick, easy setup and diagnostics
- > Compact surface-mount design
- > Includes external universal power pack

The DM-TX-100-F is a DM® Fiber transmitter that provides a single HDMI® input for a computer or high-definition AV source as part of a complete Crestron® DigitalMedia™ system. It is ideal for use at a lectern, conference table, or any remote location in a boardroom, classroom, auditorium, or residence to route an HDMI signal to a display or switcher many feet away. The DM-TX-100-F connects to the head end or display location using multimode fiber optic cable. In addition to HDMI, it includes an Ethernet port and USB HID device port for a total connectivity solution.

## DigitalMedia™ Fiber

As the leader in HDMI and control system technologies, Crestron developed DigitalMedia (DM) to deliver the first complete HD AV distribution system to take HDMI to a higher level. DigitalMedia allows virtually any mix of HDMI and other AV sources to be distributed throughout a home, office, school, or virtually any other facility. DigitalMedia Fiber distributes uncompressed digital video and audio signals up to 1000 feet (300 m) using multimode fiber optic cable<sup>[1]</sup>.

## Multimedia Computer/AV Interface

Via its HDMI input, the DM-TX-100-F supports HD 1080p60 video and WUXGA computer signals with HDCP, Deep Color, 3D, and multi-channel HD lossless audio. It can also handle DVI and DisplayPort Multimode signals using an appropriate adapter or interface cable<sup>[2]</sup>.

A single DM Fiber output is provided for connection to a DM switcher or receiver.<sup>[1]</sup> Used with a single DM Fiber Receiver/Room Controller and optional Crestron Control System, the DM-TX-100-F affords a simple solution for extending a multimedia computer or AV signal to a single display up to 1000 feet (300 m) away<sup>[1]</sup>. As part of a larger system using a DM-MD series switcher, multiple DM-TX-100-Fs may be installed to enable the distribution of several sources at different locations to feed multiple displays throughout any room or larger facility.

## LAN Connectivity

Along with high-definition AV and control, DigitalMedia also integrates high-speed Ethernet networking for a total signal distribution solution. The DM-TX-100-F includes a 10/100 Ethernet port, providing a convenient LAN connection for a local network device.



## Keyboard/Mouse Extender

The DM-TX-100-F also functions as a keyboard/mouse extender, providing a USB port which connects to the source device (i.e. computer or other USB HID-compliant host), allowing it to be controlled by a mouse or keyboard located in another room, or at a presentation lectern, conference table, or some other remote location.

## Embedded Device Control

The primary objective of every Crestron system is to enable precisely the control desired for a seamless user experience. The DM-TX-100-F includes built-in IR and Ethernet control ports to allow programmable control of the devices connected to it. But, it can also provide an alternative to such conventional control methods by harnessing the CEC (Consumer Electronics Control) signal embedded in HDMI. Through its connection to the control system, the DM-TX-100-F provides a gateway for controlling the connected source device right through the HDMI connection, potentially eliminating the need for any dedicated control wires or IR emitters.

## Compact and Versatile

The DM-TX-100-F is designed to be mounted to a flat surface, placed on a shelf, or attached to a rack rail in the back of an equipment cabinet. It may also be used portably for connection to a DM wall plate input ([MP-WP186](#) sold separately). It is compact enough to fit discreetly inside a presentation lectern or beneath a table. An array of indicators on the front of the DM-TX-100-F provides for easy setup and troubleshooting. Advanced configuration is enabled through [Crestron Toolbox™](#) software.

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

# DM-TX-100-F DigitalMedia™ Fiber Transmitter 100



DM-TX-100-F – Top, Front, & Bottom Views

## SPECIFICATIONS

### Video

**Input Signal Type:** HDMI®, DVI<sup>[2]</sup>, DisplayPort Multimode<sup>[2]</sup>

**Output Signal Type:** DM® Fiber (DigitalMedia™ over multimode fiber optic cable)

**Formats:** HDMI w/Deep Color & 3D, DVI, HDCP content protection support

**Input Resolutions, Progressive:** 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Input Resolutions, Interlaced:** 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Output Resolutions:** Matched to input

### Audio

**Input Signal Type:** HDMI, DisplayPort Multimode<sup>[2]</sup>

**Output Signal Type:** DM Fiber

**Formats:** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, Up to 8ch PCM

### Communications

**DigitalMedia:** DM Fiber, HDCP management, CEC

**Ethernet:** 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP

**USB:** Supports USB HID class devices

### Connectors

**HDMI IN:** (1) 19-pin Type A HDMI female; HDMI digital video/audio input; Also supports DVI and DisplayPort Multimode<sup>[2]</sup>

**USB HID:** (1) USB Type B female, USB device port for connection to the USB host interface of a computer or other USB HID-compliant host

**LAN:** (1) 8-wire RJ45 female; 10Base-T/100Base-TX Ethernet port

**IR:** (1) 2-pin 3.5mm detachable terminal block, IR/Serial port; IR output up to 1.1 MHz;

1-way serial TTL/RS-232 (0-5 Volts) up to 19200 baud

**DM OUT, D & M:** (1) DM Fiber output composed of (2) SC female optical fiber connectors; Connects to DM Fiber input of a DM switcher, receiver/room controller, or other DM device via CresFiber® 8G fiber optic cable<sup>[1]</sup>

**DM OUT, G 24:** (1) 2-pin 3.5mm detachable terminal block, 24 Volt DC power input; PW-2407WUL power pack included

# DM-TX-100-F DigitalMedia™ Fiber Transmitter 100

**G:** (1) 6-32 screw, chassis ground lug

## Controls & Indicators

**PWR:** (1) green LED, indicates operating power supplied via power pack

**DM LINK:** (1) green LED, indicates DM link status

**HDMI IN:** (1) green LED, indicates HDMI input signal presence and lock status

**SETUP:** (1) red LED and (1) miniature recessed pushbutton for Ethernet setup

**RESET:** (1) miniature recessed pushbutton for hardware reset

**LAN:** (2) LEDs, green LED indicates Ethernet link status, amber LED indicates Ethernet activity

## Power Requirements

**Power Pack:** 0.75 Amps @ 24 Volts DC;

100-240 Volts AC, 50/60 Hz power pack, model PW-2407WUL included

## Environmental

**Temperature:** 32° to 104°F (0° to 40°C)

**Humidity:** 10% to 90% RH (non-condensing)

**Heat Dissipation:** 31 BTU/Hr

## Enclosure

**Chassis:** Aluminum w/polycarbonate label overlay and (4) integral mounting flanges

**Mounting:** Freestanding, surface mount, or attach to a single rack rail

## Dimensions

**Height:** 7.60 in (193 mm)

**Width:** 4.56 in (116 mm)

**Depth:** 1.43 in (37 mm)

## Weight

19.8 oz (562 g)

## MODELS & ACCESSORIES

### Available Models

DM-TX-100-F: DigitalMedia™ Fiber Transmitter 100

### Included Accessories

PW-2407WUL: Wall Mount Power Pack 24VDC, 0.75A, Universal (Qty. 1 included)

### Available Accessories

**CRESFIBER8G-NP:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

**CRESFIBER8G-P:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

**CRESFIBER-CONN-SC50UM-12:** CresFiber® Fiber Optic Cable Connector (AFL Telecommunications™), SC 50µm, 12-Pack

**CRESFIBER-TK:** CresFiber® Termination Kit (AFL Telecommunications™)

**CRESFIBER-DUAL-SC-P:** CresFiber® Duplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

**CRESFIBER-DUAL-SC-ARMORED-P:** CresFiber® ARMORED Duplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum

**CRESFIBER-SINGLE-SC-CLEAR-NP:** CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum

**CBL Series:** Crestron® Certified Interface Cables

**MP-WP Series:** Media Presentation Wall Plates

**MPI-WP Series:** Media Presentation Wall Plates - International Version

**IRP2:** IR Emitter Probe

### Notes:

1. The maximum DigitalMedia Fiber cable length is 1000 ft (300 m) using [CRESFIBER](#), [CRESFIBER8G](#), [CRESFIBER-DUAL-SC](#), or generic OM2/OM3 duplex multimode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All cable sold separately.
2. HDMI requires an appropriate adapter or interface cable to accommodate a DVI or DisplayPort Multimode signal. [CBL-HD-DVI](#) interface cables available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

CresFiber, Crestron, Crestron Toolbox, DigitalMedia, DM, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

# DM-TX-100-F DigitalMedia™ Fiber Transmitter 100

