


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	DM Lite 4K Multiformat Switch and Receiver
Name and address of the applicant	Crestron Electronics, Inc. 15 Volvo Drive, Rockleigh, New Jersey 07647, USA
Name and address of the manufacturer	ASKEY COMPUTER CORP 5-10F 119 Jiankang Rd Zhonghe District New Taipei, 23585 TAIWAN
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	ASKEY COMPUTER CORP 5-10F 119 Jiankang Rd Zhonghe District New Taipei, 23585 TAIWAN
Ratings and principal characteristics	<input type="checkbox"/> Additional Information on page 2 Input: 100-240 V~, 4-2 A, 50/60 Hz
Trademark / Brand (if any)	
Type of Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	M1845002
Additional information (if necessary may also be reported on page 2)	The report was revised to include technical modification(s). <input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	CB0062007179A issued on 2020-09-04

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnamesDate: 2020-09-09
Original Issue Date: 2019-07-29

Signature:

Jan-Erik Storgaard

Additional Information:

Additionally evaluated to EN 62368-1:2014 /A11:2017.
National Difference specified in the CB Test Report.

The original report was modified to include the following changes/additions:

01. Change the ES1 circuit and layout of main board slightly for following.

- a. Enhance the interoperability for HDMI function.
- b. Improve the Noise Pop for AUX 1/2.
- c. Improve the efficiency for Audio Mic function.
- d. Due to the better protection, change the components from RP27/RP25 to D61/D62.
- e. Due to the EMI concern, change the capacitance from 1000 pF to 0.15 uF for C325, C342, C360, C361, C362 and C363.

02. Add interchangeable button base.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA



UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK



UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN



UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2020-09-09

Original Issue Date: 2019-07-29

Signature:



Jan-Erik Storgaard