



CONTINUOUS BLOCKING /
STRUCTURAL SUPPORT MUST
BE LEVEL (BY OTHERS)

ARCHITECTURAL 5 SERIES
BRACKET WITH QMT5
MOTOR & 2.5" Ø TUBE
REGULAR ROLL

Ø4"
[Ø102MM]
MAX.
R.U.D.

Ø4"
[Ø102MM]
MAX.
R.U.D.

10"
[254MM]
SHADE HEIGHT

SHADE OPENING

WINDOW MULLION
(BY OTHERS)

1/16"
[2MM]

3"
[76MM]

3 15/16"
[100MM]

7"
[178MM]

HEM BAR IN UP
POSITION

REAR FABRIC IN
DOWN POSITION

FRONT FABRIC IN
DOWN POSITION

CEILING
(BY OTHERS)

QMT5 ARCHITECTURAL DUAL SHADE
IN A GYPSUM POCKET REVERSE MOUNT
WITH POCKET FLAP
CEILING MOUNT



15 VOLVO DRIVE
ROCKLEIGH NJ 07647
TEL: 888-273-7876
WWW.CRESTRON.COM

DWG. #	MA5D-103
SCALE:	6" = 1'-0"
DATE:	11.10.2016
REV.:	