

## Zūm™ Wireless Battery-Powered Occupancy Sensor

- > Zūm™ wireless ceiling-mount occupancy sensor
- > Passive infrared motion detection
- > 360 degrees, 500 sq ft (46.5 m<sup>2</sup>) coverage
- > Half mask and perforated mask included
- > Detects room occupancy and vacancy
- > Automates control of Zūm dimmers, switches, and load controllers to reduce energy usage<sup>[1]</sup>
- > Turns lights on when the room is occupied and off when the room is vacant
- > 10-year battery life using included 9 Volt lithium battery
- > Zūm Mesh peer-to-peer RF communications for easy integration into a complete standalone or networked Zūm wireless lighting control solution<sup>[2]</sup>
- > Discreet, low-profile appearance
- > Meets UL® 916 standard for energy management equipment
- > Meets CEC Title 24 energy efficiency standards<sup>[3]</sup>
- > Meets ASHRAE® 90.1 energy efficiency standards<sup>[4]</sup>
- > ICC® International Energy Conservation Code® compliant<sup>[5]</sup>

A Zūm™ occupancy sensor offers a cost-saving solution for reducing energy usage in rooms equipped with a Zūm commercial room lighting system. The **ZUMMESH-PIR-OCCUPANCY-BATT** is a passive infrared occupancy sensor designed for ceiling mount installation in areas up to 500 square feet or 46.5 square meters. It communicates wirelessly with a Zūm **dimmer**, **switch**, or **load controller** to turn lights on and off automatically based on room occupancy and vacancy.<sup>[1]</sup> Up to eight occupancy sensors may be employed for increased coverage.

The ZUMMESH-PIR-OCCUPANCY-BATT is battery powered and completely wireless. It operates for up to ten years or more on a single 9 Volt lithium battery (included). Zūm Mesh wireless technology affords easy “pair and play” setup and integration as part of a complete Zūm commercial room lighting system.<sup>[2]</sup>

Featuring passive infrared (PIR) technology, the ZUMMESH-PIR-OCCUPANCY-BATT employs a highly sensitive specialized lens that divides the field-of-view into sensor zones. The sensor detects motion when a warm body passes between zones, achieving dependable motion detection with superior immunity to false triggering from vibrations, inanimate objects, or movement in an adjacent corridor. The detection sensitivity is adjustable for optimum performance. Timeout can be set anywhere from 30 seconds to 30 minutes to maintain occupied status during short periods of inactivity. A half mask and perforated mask are included to customize the coverage area.

Please refer to the Zūm Lighting Control System Setup Guide ([Doc # 7957](#)) for additional information.



### SPECIFICATIONS

#### Sensing

**Sensor Technology:** Passive infrared

**Coverage Area:** 500 square feet (46.5 square meters)

**Coverage Pattern:** 360 degrees (half mask and perforated mask included)

**Major Motion Area:** 150 to 500 square feet (13.9 to 46.4 square meters)

**Minor Motion Area:** 0 to 150 square feet (0 to 13.9 square meters)

*Note: A maximum of eight occupancy sensors is permitted per room; do not combine occupancy sensors with vacancy sensors in the same room.*

#### Wireless Communications

**RF Transceiver:** Zūm Mesh 2-way RF, 2.4 GHz ISM Channels 15, 20, 25, or 26 (channel auto-selected), IEEE 802.15.4 compliant

**Range:** 50 ft (15 m) to nearest peer-to-peer mesh network device(s), subject to site-specific conditions and individual device capabilities<sup>[2]</sup>

*Note: A maximum of 32 Zūm Mesh wireless devices is permitted per room.*

#### Controls & Indicators

**Sensitivity:** (1) Knob (behind cover), adjusts PIR sensitivity from low to high

**Timeout:** (1) Knob (behind cover), adjusts timeout from 30 seconds to 30 minutes

**Test:** (1) Pushbutton (behind cover) for test mode, room setup, factory reset, and battery condition

**Status:** (1) Red and (1) green LEDs for test mode, room setup, factory reset, and battery condition

#### Power

**Battery:** (1) Ultralife® U9VL-J-P 9 Volt 1200 mAh lithium disposable battery (included)

**Battery Life:** 10 years under normal operating conditions

# ZUMMESH-PIR-OCCUPANCY-BATT Züm Wireless Battery-Powered Occupancy Sensor

## Environmental

**Temperature:** 32° to 104° F (0° to 40° C)

**Humidity:** 0% to 95% RH (non-condensing)

## Construction

**Housing:** Plastic, removable cover, white finish

**Mounting:** Ceiling surface mount, 3 inch (76 mm) screw spacing

## Dimensions

**Height:** 1.19 in (31 mm)

**Diameter:** 4.38 in (112 mm)

## Weight

**Without Battery:** 3.5 oz (98 g)

**With Included Battery:** 4.8 oz (135 g)

## Compliance

UL Listed for US & Canada, CE, IC, FCC Part 15 Class A digital device, UL 60730-1, UL 916, CEC Title 24 [3], ASHRAE 90.1 [4], IECC [5]

## MODELS & ACCESSORIES

### Available Models

**ZUMMESH-PIR-OCCUPANCY-BATT:** Züm Wireless Battery-Powered Occupancy Sensor

### Available Accessories

**ZUMMESH-JBOX-5A-LV:** Züm J-Box Load Controller, 0-10V Dimmer, 5A, 100-277V

**ZUMMESH-JBOX-16A-LV:** Züm J-Box Load Controller, 0-10V Dimmer, 16A, 100-277V

**ZUMMESH-JBOX-20A-SW:** Züm J-Box Load Controller, High Inrush Switch, 16A, 100-277V

**ZUMMESH-JBOX-20A-PLUG:** Züm J-Box Load Controller, Plug Load Switch, 20A, 100-240V

**ZUMMESH-5A-LV:** Züm Wireless 0-10V Wall-Box Dimmer, 5A, 100-277V

**ZUMMESH-5A-SW:** Züm Wireless Wall-Box Switch, 5A, 100-277V

## Notes:

1. Item(s) sold separately. Refer to each product's spec sheet for more information.
2. "Züm Mesh" refers to the peer-to-peer wireless mesh network within a room composed of dimmers, switches, load controllers, keypads, and sensors. AC-powered Züm Mesh devices function as routing nodes, which effectively extend the range of the wireless network within the room. The ZUMMESH-PIR-OCCUPANCY-BATT and other battery-powered devices only function as leaf nodes and do not extend range. Networks composed predominantly of battery-powered devices may require additional AC-powered devices, such as the ZUMMESH-JBOX-PSU, to serve as supplemental routing nodes to fill any gaps in coverage. Refer to the "Installation and Setup of Crestron RF Products, Best Practices" guide (Doc #6689) for additional guidelines.
3. This product is part of a California Energy Commission Title 24 compliant solution. Refer to <http://www.energy.ca.gov/title24/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.
4. This product is part of an ASHRAE 90.1 compliant solution. Refer to <https://www.ashrae.org/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.
5. This product is part of an International Energy Conservation Code compliant solution. Refer to <https://www.iccsafe.org/iecc/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.

This product may be purchased from an authorized Crestron dealer or distributor. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>. For assistance with incorporating this product into a design or specification, please contact the Commercial Lighting Consultant Hotline via email at [clcdesign@crestron.com](mailto:clcdesign@crestron.com) or by calling 888-330-1502.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, and Züm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. ASHRAE is either a trademark or registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. in the United States and/or other countries. ICC and International Energy Conservation Code are either trademarks or registered trademarks of International Code Council, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of UL LLC in the United States and/or other countries. UltraLife is either a trademark or a registered trademark of UltraLife Corporation in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.

©2017 Crestron Electronics, Inc.

