

## 4-Series™ Control System



- 4-Series control system with 2 GB SDRAM and 8 GB flash memory
- Embedded 4-Series™ multicore CPU processor
- iPhone®, iPad®, and Android™ device control app support
- XPanel computer and web-based control
- Modular programming architecture
- Front panel color LCD display for setup and diagnostics
- Onboard IR/serial, COM, I/O, relay, Cresnet® network, and high-speed gigabit Ethernet control ports
- Control subnet ports with PoE+ providing a dedicated local network for Crestron® devices
- High-speed USB 2.0 host port and rear panel memory card slot
- Three built-in control card expansion slots (optional)
- IEC 61000-4-5 Installation Class 4 surge immunity on COM, Versiport, and network connections
- Support for Crestron Fusion® software and XiO Cloud® service
- Native .AV Framework™ software program
- Enterprise-class network security and authentication
- SNMP V3 remote IT management support
- Native BACnet network/IP support
- Installer setup via front panel, software, web browser, or cloud
- IPv6 ready
- Integrates with Apple® HomeKit® technology
- Rack mountable

The PRO4 is a secure, high-performance control processor with a powerful 4-Series control engine and an enhanced feature set, including a front panel color LCD display, built-in control card expansion slots, and dedicated control subnet ports. The PRO4 is designed to integrate and automate technology within any modern networked home, commercial building, or government facility. The isolated control subnet port provides a Gigabit Ethernet LAN dedicated to Crestron devices.

### 4-Series Control Engine

4-Series control systems come equipped with an upgraded multicore CPU, delivering a sizable speed and performance increase compared to all Crestron 3-Series® control processors. The improved performance allows 4-Series control systems to handle the increasing demands of an advanced automated system. Crestron 4-Series delivers a dynamic and secure control system platform capable of managing a room full of disparate technologies.

Reliable networking and IP control afford seamless integration with other systems and devices, with add-on control capability using Crestron touch screens, wireless remotes, and mobile device apps, as well as remote management through Crestron Fusion® software and the XiO Cloud® service.

### Modular Programming Architecture

The PRO4 provides a modular programming architecture that allows it to run up to ten programs simultaneously. Programmers can develop and run independent, device-specific programs, enabling each program to be optimized for a specific function and allowing for changes to be made to one program without affecting the whole system.

### Dedicated Control Subnet

The Crestron Control Subnet is a Gigabit Ethernet network dedicated to Crestron devices. Via the Control Subnet ports, an installer can connect up to four touch screens or wireless gateways or can add Crestron PoE switches ([CEN-SW-POE-5](#) or [CEN-SWPOE-16](#), both sold separately) to handle multiple touch screens, gateways, AV components, and other devices. Each port also supports PoE+ using the optional [PW-5430DUS](#) power supply (sold separately). Auto-configuration of the entire subnet is performed by the PRO4, discovering each device and assigning IP addresses without any extra effort from the installer.<sup>1</sup>

A separate LAN port provides a single-point connection to the local network, requiring only one IP address for the entire control system. The LAN port allows for interconnectivity between devices on the local subnet and other devices, systems, servers, and WAN/internet connections outside the local subnet. For sensitive applications that require heightened security, the entire Control Subnet can be isolated completely from the local network.

### Onboard Control Ports

Through a full complement of onboard control ports, the PRO4 can be integrated with a wide variety of audio, video, lighting, motorized shades, thermostats, door locks, sensors, security systems, and other equipment.<sup>1</sup>

- Gigabit Ethernet provides an interface for connecting to the building network and controlling Crestron AV switchers, audio processors, power controllers, and other IP controllable equipment.

## 4-Series™ Control System

- Cresnet® network connectivity provides support for Crestron lighting dimmers, motorized shades, sensors, thermostats, keypads, and more.
- Onboard RS-232, IR/serial, relay, and Versiport I/O control ports enable direct integration with all types of third-party equipment.

Expanded connectivity can be provided to the PRO4 via Crestron [control port expansion modules](#), [Ethernet to Cresnet bridges](#), [wired Ethernet I/O modules](#), [wireless network I/O modules](#), or [infiNET EX® network wireless gateways](#) (all sold separately).

### Crestron Fusion Room Monitoring and Scheduling

Crestron Fusion provides an integrated platform for creating smart buildings that save energy and enhance worker productivity. As part of a complete managed network, the PRO4 works with Crestron Fusion to enable remote scheduling, monitoring, and control of rooms and technology from a central help desk or mobile app. It also enables organizations to reduce energy consumption by tracking real-time usage and automating control of AV, lighting, shades, and HVAC. For more information about Crestron Fusion, visit [www.crestron.com/fusion](http://www.crestron.com/fusion).

### XiO Cloud Provisioning and Management

4-Series control systems leverage the power and flexibility of XiO Cloud services, enabling users to remotely provision, monitor, and manage Crestron devices across an enterprise network. XiO Cloud can be used to configure and load programs to the control system before it is received, making the control system fully functional as soon as it is connected to the network. Crestron XiO Cloud is built on the Microsoft® Azure® software platform and utilizes Microsoft's industry leading Azure IoT Hub technology. XiO Cloud enables installers and IT managers to deploy and manage thousands of devices simultaneously. Unlike other virtual machine based cloud solutions, Azure services provide unlimited scalability to suit the ever growing needs of an enterprise. For more information, visit [www.crestron.com/xiocloud](http://www.crestron.com/xiocloud).

### .AV Framework Software

The PRO4 provides native support for the .AV Framework™ software program. .AV Framework software is a web-based management solution that is used to deploy scalable Crestron® enterprise room solutions without requiring any programming. For more information on the capabilities supported by .AV Framework, visit [www.crestron.com/avframework](http://www.crestron.com/avframework).

### Enhanced Enterprise-Grade Security

The PRO4 is an enterprise-class control processor that can be deployed across hundreds of spaces and set up easily using the front panel LCD display, a web browser, Crestron Toolbox™ software, or XiO Cloud. It employs standard network security protocols, including 802.1X network access control, Active Directory® service authentication, SSH, TLS, and HTTPS to ensure reliability and compliance with your organization's IT policies.

The PRO4 is configured to meet Crestron's enhanced security standards right out of the box. The PRO4 ships with authentication enabled and requires that an administrator account be created before access is granted to device configuration and control interfaces.

### SNMP V3 Support

Built-in SNMP V3 support enables integration with third-party IT management software, allowing network administrators to manage and control Crestron systems on the network in an IT-friendly format.

### Front Panel LCD Display

The PRO4 front panel includes a color LCD display to enable extensive setup and diagnostics without having to connect a computer.

### Control Card Expansion Slots

Additional control ports can be added to the PRO4 using [control cards](#). The PRO4 provides three control card expansion slots on its rear panel, affording great expansion capability without requiring any additional rack space. The CAGE3 accessory installs in the AV4, providing three control card expansion slots on the AV4 rear panel. Adding the CAGE3 option affords great expansion capability without requiring any additional rack space.

### BACnet Support

Native support for the BACnet communication protocol provides a direct interface to third-party building management systems over Ethernet, simplifying integration with HVAC, security, and other systems. Using BACnet, each system runs independently but communicates together on one platform.<sup>1</sup>

### Apple HomeKit Integration

The PRO4 supports integration with an Apple® HomeKit® technology system. Once the PRO4 is paired with a HomeKit system via [SIMPL](#) programming, a Crestron [TSR-310](#) can be used to control supported Apple devices. A pairing QR code is affixed to the PRO4 that makes it easy to pair the control system directly to the Apple Home app.<sup>2</sup>

## 4-Series™ Control System

### Specifications

#### Control Engine

Crestron® 4-Series™; real-time, preemptive multi-threaded/multitasking kernel; supports up to 10 simultaneously running programs, native .AV Framework™ software program

#### Communications

**Ethernet** 100/1000 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, industry-standard TCP/IP stack, UDP/IP, CIP, DHCP, SSL, TLS, SNMP, SSH, SFTP (SSH File Transfer Protocol), FIPS 140-2 compliant encryption, IEEE 802.1xX, SNMP, BACnet and IP<sup>1</sup>, IPv4 or IPv6, Active Directory® service authentication, HTTPS web server, HTTPS web browser setup and XiO Cloud® client, SMTP email client

**Control Subnet** 100/1000 Mbps Ethernet, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP server, DNS server, port forwarding, isolation mode, IEEE 802.3at Type 1 compliant PoE PSE

**Cresnet® Network** Cresnet master mode

**USB** Supports USB mass storage class devices via the rear panel USB 2.0 host port, supports computer console via the front panel USB 2.0 device port

**RS-232/422/485** For 2-way device control and monitoring, COM port supports RS-232 up to 115.2k baud with software handshaking, one port also supports RS-422 or RS-485 and hardware handshaking

**IR/Serial** Supports 1-way device control via infrared up to 1.2 MHz or serial TTL/RS-232 (0–5V) up to 115.2k baud

#### Memory

**SDRAM** 2 GB

**Flash** 8 GB

**Memory Card** Supports SD and SDHC cards up to 32 GB

**External Storage** Supports USB storage devices up to 1 TB

#### Connectors and Card Slots

**S1–S3** (3) control card expansion slots

**COM 1–2** (2) 5-pin 3.5 mm detachable terminal blocks; Bidirectional RS-232/422/485 ports; Up to 115.2k baud; hardware and software handshaking support

**COM 3–6** (4) 3-pin 3.5 mm detachable terminal blocks; Bidirectional RS-232 ports; Up to 115.2k baud; software handshaking support

**IR - SERIAL OUTPUT 1–8** (2) 8-pin 3.5 mm detachable terminal blocks; Comprises (8) IR output ports; IR output up to 1.2 MHz; 1-way serial TTL/RS-232 (0–5V) up to 115.2k baud; IRP2 IR emitters sold separately

**RELAY OUTPUT 1–8** (2) 8-pin 3.5 mm detachable terminal blocks; Comprises (8) normally open, isolated relays; Rated 1 A, 30VAC/VDC; MOV arc suppression across contacts

**PoE+ INPUT POWER** (1) Combo D-Sub 7w2 connector, male; 54VDC power input for PoE+ power supply; Enables PoE+ power sourcing on the CONTROL SUBNET ports

**CONTROL SUBNET** (4) 8-pin RJ-45 connectors, female; 100BASE-TX/1000BASE-T Ethernet port; PoE+ PSE (Power Sourcing Equipment) port; Provides a dedicated local network for Crestron devices

**LAN** (1) 8-pin RJ-45 connector, female; 100BASE-TX/1000BASE-T Ethernet port;

**USB** (1) USB Type A connector, female; USB 2.0 port for storage devices

**MEMORY** (1) SD memory card slot; Accepts one SD or SDHC card up to 32 GB for storage of log files

## 4-Series™ Control System

<b>I/O 1-8</b>	(1) 9-pin 3.5 mm detachable terminal block; Comprises (8) Versiport digital input/output or analog input ports (referenced to GND); Digital Input: Rated for 0–24VDC, input impedance 20k $\Omega$ , logic threshold >3.125V low/0 and <1.875V high/1; Digital Output: 250 mA sink from maximum 24VDC, catch diodes for use with real world loads; Analog Input: Rated for 0–10VDC, protected to 24VDC maximum, input impedance 21k $\Omega$ with pull-up resistor disabled; Programmable 5V, 2k $\Omega$ pull-up resistor per pin	<b>HW-R</b>	(1) Recessed push button, initiates hardware reset
<b>NET</b>	(1) 4-pin 3.5 mm detachable terminal block; Cresnet master port; Outputs power to Cresnet devices; Alternately functions as a Cresnet power input to power the unit from a Cresnet power supply; See "Power" section below for additional details	<b>SW-R</b>	(1) Recessed push button, initiates software reset
<b>100–240V~ 2.4A 50/60Hz</b>	(1) IEC 60320 C14 main power inlet; Mates with removable power cord	<b>CNPS FAULT</b>	(1) Red LED and (1) push button; LED indicates an excessive Cresnet load detected at the NET port; Push button resets the fault indication
<b>G</b>	(1) 6-32 screw; Chassis ground lug	<b>SLOT 1-3</b>	(3) Green LEDs, indicate control cards are inserted in the corresponding slots
<b>COMPUTER (front)</b>	(1) USB Type B connector, female; USB 2.0 computer console port; For setup only	<b>Nav Pad</b>	(1) 5-way navigation pad for LCD display menu navigation and parameter adjustment
<b>LCD Display</b>		<b>HOME</b>	(1) Push button, returns to the LCD display home menu
<b>Display Type</b>	TFT active matrix color LCD	<b>BACK</b>	(1) Push button, returns back one level on the LCD display
<b>Size</b>	2.8 in. (72 mm) diagonal	<b>LAN (rear)</b>	(1) Bicolor green/amber and (1) Amber LEDs; Green/amber LED indicates Ethernet link status and connection speed; Amber LED indicates Ethernet activity
<b>Resolution</b>	320 x 240 pixels	<b>CONTROL SUBNET (rear)</b>	(1) Bicolor green/amber and (1) Amber LEDs; Green/amber LED indicates Ethernet link status and connection speed; Amber LED indicates Ethernet activity
<b>Functions</b>	Displays configuration menus, control port activity, and other system information		
<b>Controls and Indicators</b>			
<b>PWR</b>	(1) Bicolor Green/Amber LED, indicates operating power is present; Amber indicates that the device is booting and is not yet ready to operate; Green indicates that the device is ready to operate		
<b>NET</b>	(1) Amber LED, indicates communication with Cresnet devices		
<b>MSG</b>	(1) Red LED, indicates control processor has generated an error message		
		<b>Power</b>	
		<b>Main Power</b>	2.4A @ 100-240VAC, 50/60Hz
		<b>Available Cresnet Power</b>	75W (3.125A @ 24VDC)
		<b>Power over Ethernet Plus (PoE+)</b>	IEEE 802.3at compliant PoE+ PSE (Power Sourcing Equipment); 120W total power; Each CONTROL SUBNET port supplies up to 30W to power one PoE+ (Class 4) PD (Powered Device)
		<b>Environmental</b>	
		<b>Temperature</b>	41 to 104°F (5 to 40°C)
		<b>Humidity</b>	10% to 90% RH (noncondensing)
		<b>Heat Dissipation</b>	43 BTU/hr
		<b>Enclosure</b>	
		<b>Chassis</b>	Metal, black finish, vented top and sides
		<b>Faceplate</b>	Extruded metal, black finish, polycarbonate label overlay
		<b>Mounting</b>	Freestanding or 2 RU 19-in. rack-mountable (adhesive feet and rack ears included)

# PRO4

## 4-Series™ Control System

### Dimensions

---

Height	3.47 in. (89 mm) without feet
Width	17.28 in. (439 mm); 19.00 in. (483 mm) with rack ears
Depth	10.15 in. (258 mm)

### Weight

---

11.02 lb (5.0 kg)

### Compliance

---

**Regulatory Model: M201903001;**

BV Listed for US & Canada, CE, IC, FCC Part 15 Class B digital device

### Models

**PRO4**  
4-Series™ Control System

### Available Accessories

For supported accessories, visit the PRO4 product page at [www.crestron.com](http://www.crestron.com).

#### Notes:

1. The following connections comply with IEC 61000-4-5 Installation Class 4 surge immunity levels: COM 1-6, I/O 1-8, NET, LAN, and CONTROL SUBNET.
2. A BACnet and IP license is required. A free license is available to support up to 50 BACnet objects on a single 4-Series control system. Enabling support for more than 50 BACnet objects requires the purchase of one [SW-3SERIES-BACNET-50+](#) license. The PRO4 supports a maximum of 2000 BACnet objects when dedicated for BACnet use only. Actual capabilities are contingent upon the overall program size and complexity. To obtain the license, visit [www.crestron.com/bacnetlicense](http://www.crestron.com/bacnetlicense).
3. This feature is only available when using the TSR-310. Other Crestron touch screens, handheld remotes, and keypads are not supported. For these interfaces, traditional IR or CEC control must be used to control supported Apple devices.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, 3-Series, 4-Series, .AV Framework, Cresnet, Crestron Fusion, Crestron Toolbox, infiNET EX, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Apple, HomeKit, iPad, iPhone, and iPod touch are either trademarks or registered trademarks of Apple, Inc. in the United States and/or other countries. Android is either a trademark or a registered trademark of Google Inc. in the United States and/or other countries. Active Directory, Azure, and Microsoft are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. UL is either a trademark or a registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 01/14/22

