

ULTIMATE IGS12T-PRIMED-EACH

Ultimate 12 in. In-Ground Subwoofer, Primed Paintable, Single



- *High-performance direct-burial in-ground subwoofer*
- *Rugged poly composite PVC enclosure*
- *IPX6 waterproof*
- *12 in. (305 mm) polypropylene woofer*
- *200 W (Program), and 400 W (Peak) power handling*
- *23 Hz to 100 Hz (±3 dB) frequency response*
- *8 Ohms nominal impedance*
- *Primed finish dome-shaped paintable port cap*
- *Built-in 300 W toroidal transformer for high impedance connectivity*

The Crestron® ULTIMATE IGS12T-PRIMED-EACH in-ground subwoofer made by Origin Acoustics provides the full impact of your music outdoors with rich and deep bass. Its compact, watertight enclosure installs beneath the ground's surface, affording a virtually hidden appearance with just the port tube visible. The port tube protrudes 7.20 inches from the ground and is topped with a paintable dome-shaped cap, providing a subdued appearance.

The ULTIMATE IGS12T-PRIMED-EACH is a passive in-ground subwoofer, employing 12 in. woofer for tight, controlled bass. Power handling is 200 Watts (Program), and 400 W (Peak) at 8 Ohms, with a frequency response of 23 Hz to 100 Hz (±3 dB).

The ULTIMATE IGS12T-PRIMED-EACH includes a 44 in. (1118 mm) direct-burial speaker wire that is permanently attached to the speaker enclosure. A suitable in-ground electrical box (not included) is advised for termination of the speaker and transformer wiring. A pair of waterproof wire nuts are included to terminate the bare wire ends.

Specifications

Features & Performance

Woofer	12 in. (305 mm) polypropylene
Impedance	8 Ohms nominal
Transformer Taps	150 W @ 70V; 300 W @ 100V
Frequency Response	23 Hz to 100 Hz (±3 dB)
Power Handling	Program: 200 W; Peak: 400 W
Sensitivity	86 dB @ 1 W/1 m

Connections

Input	(1) 44 in. (1118 mm) attached direct-burial speaker wire; Includes one pair of silicone filled waterproof wire nuts
Maximum Wire Size	(2) 12 AWG (4 mm ²)

Environmental

Temperature	4° to 176°F (-15.5° to 80°C)
Humidity	10% to 90% RH (non-condensing)
Splash Resistance	IPX6 waterproof

Construction

Enclosure	Rugged poly composite PVC
In-Ground Installation	Designed for direct-burial in soil with good drainage

Dimensions

Height with port tube and cap	23.57 in. (599 mm)
Height without port tube and cap	12.05 in. (306 mm)
Width	19.69 in. (500 mm)

Weight

78.15 lb (35.44 kg)

ULTIMATE IGS12T-PRIMED-EACH

Ultimate 12 in. In-Ground Subwoofer, Primed Paintable, Single

Compliance

Regulatory Model: M202046012

CE, RoHs, FCC Part 15 Class B digital device

Models

ULTIMATE IGS12T-PRIMED-EACH

Ultimate 12 in. In-Ground Subwoofer, Primed Paintable, Single

ULTIMATE IGS12T-BRZ-T-EACH

Ultimate 12 in. In-Ground Subwoofer, Bronze Textured, Single

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Origin Acoustics is either a trademark or a registered trademark of Origin Acoustics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2021 Crestron Electronics, Inc.

Rev 07/07/21

ULTIMATE IGS12T-PRIMED-EACH

Ultimate 12 in. In-Ground Subwoofer, Primed Paintable, Single

