

# AMP-X75

## X-Series Amplifier, 75 W



- Compact, configurable ENERGY STAR® certified power amplifier
- Quarter-rack width form factor, gangable with other next generation half- and quarter-rack width form factor Crestron products
- 1 RU high design is surface or rack mountable
- Configurable for either LoZ or Hi-Z operation
- Configurable for 1 x up to 75 W output for Hi-Z or Bridged or 2 x up to 35 W output for stereo low impedance
- Low noise, low distortion, and high headroom
- Comprehensive fault and speaker protection
- Captive speaker connectors for secure and robust connectivity
- Support for two channels of balanced or unbalanced line inputs
- Stereo or mono-summed operation
- Convection cooled for noiseless operation
- Standby functionality turns on amplifier in approximately 0.1s when input sensing circuitry detects an audio signal
- Rack and surface mount parts are included
- Stereo ALS line level output for assistive listening systems
- Remote standby feature allows for instant on/off control over amplifier outputs via a simple contact closure input
- Front panel power/standby, Hi-Z, fault, and signal/clip indicators
- Internal universal 100-240V power supply

The [AMP-X75](#) is a high performance, space saving, energy efficient amplifier that's totally configurable, yet simple to use. Whether you need a stereo amplifier that mounts on a wall or under a table, or a high impedance speaker run fed from a rack mounted unit, the AMP-X75 is simple to specify and install in any configuration.

### LoZ (4/8 Ω) and Hi-Z (70V or 100V) Output

The AMP-X75 is a 2-channel amplifier (up to 35 W per single-ended, low impedance channel) which can also be configured for a single channel of bridged operation (up to 75 W for the bridged channel), or for a single channel of high impedance operation (up to 75 W) to drive a distributed speaker system (70V or 100V). Balanced and unbalanced

inputs are available for connection to a single stereo or two mono source(s) via detachable terminal blocks or a 3.5 mm TRS connector. Balanced and unbalanced inputs are summed for simultaneous use.

**NOTE:** Each configuration can output up to its respective power rating.

### Solid and Efficient Performance

The AMP-X75 is engineered to deliver exceptional performance and reliability with low distortion, low noise, and high power headroom. Advanced Class D technology maximizes efficiency to reduce power consumption and heat dissipation. An internal universal power supply ensures consistent performance at varying line voltages.

### Convection Cooling

The efficient design ensures cool running operation and long-term reliability. The AMP-X75 is high-density stackable with other Crestron modular amplifiers, allowing multiple units to be installed vertically in an equipment rack without needing extra ventilation space.

### Modular Design

The AMP-X75 is housed in a quarter-width rack-mountable form factor that can be installed individually or ganged together with other units in a single rack space. The amplifier ships complete with all the hardware required for installation. Rack and surface mount parts are included, so there are no other mounting accessories or rack shelves to purchase. Whether mounting in a rack, attaching to a flat surface, or placing on a shelf, it's easy to combine multiple amplifiers into a single assembly. Additional or replacement X-Series amplifier mounting hardware is available for purchase as the [RMK-AMP-X](#) mounting kit.

### Fully Protected

The AMP-X75 features protection against overheating, shorted or overloaded speaker lines, excessive input signals, and other faults. In the case of a shorted speaker line or overheating condition, outputs mute automatically until the fault condition is resolved. In the event of a prolonged fault, such as an internal component failure, the outputs mute instantly and the amplifier shuts down.

### ENERGY STAR® Certified

An energy-efficient design enables the AMP-X75 to meet demanding ENERGY STAR requirements. In addition to its high efficiency operation, the AMP-X75 powers down automatically when no input signal is detected for more than 25 minutes, reducing overall power consumption and heat as part of an Energy Star® compliant system design. The amplifier quickly powers back on the instant an input signal is detected. A remote input can connect to a contact closure to place the amplifier in standby mode.

# AMP-X75

## X-Series Amplifier, 75 W

### Specifications

#### Audio

##### Output Power

Mode	1 Channel Driven	2 Channels Driven
LoZ, 8 ohm (single ended)	35 W	35 W
LoZ, 4 ohm (single ended)	35 W	35 W
LoZ, 8 ohm Bridged	75 W	N/A
Hi-Z 70V	75 W	N/A
Hi-Z 100V	75 W	N/A

<b>Input Signal Types</b>	Balanced or unbalanced analog line-level
<b>Frequency Response</b>	20 Hz to 20 kHz $\pm 0.5$ dB at 1 W
<b>High-Pass Filter (70V and 100V operation only)</b>	-3 dB @ 80 Hz, -12 dB/octave
<b>THD+N</b>	<0.1% at 1 kHz @ -3 dB full rated output power
<b>S/N Ratio</b>	>103 dBA, 20 Hz to 20 kHz, balanced
<b>Crosstalk</b>	-75 dB at 1 kHz
<b>Input Sensitivity</b>	1.23 Vrms, +4 dBu balanced; 0.316 Vrms, -10 dBV unbalanced; For 35 W (8 Ohms), 75 W (70V/100V)
<b>Gain</b>	23 dB @ 8 Ohms, Balanced Input
<b>Protection</b>	Clipping, over current, under voltage, over temperature, DC offset, extreme high frequency
<b>Standby Mode</b>	25 minutes with no signal present, typical
<b>Wake Time</b>	0.1 s typical
<b>Wake Threshold</b>	0.44 mV typical

#### Connectors

<b>SPEAKER OUTPUT</b>	(1) 4-pin 5.08 mm pitch, 12A plug with screw locking retainers; Power amplifier output; Wire Size: Terminals accept up to 12 AWG (3.31 mm <sup>2</sup> )
-----------------------	--

**NOTE:** Output is direct-coupled, not transformer isolated.

<b>AUDIO IN (UNBALANCED)</b>	(1) 3.5 mm TRS connector, female; Unbalanced line-level audio inputs; Maximum Input Level: 2.24 Vrms, +7 dBV (+9.2 dBu)
<b>AUDIO IN (BALANCED)</b>	(2) 3-pin 3.5 mm detachable terminal block; Balanced line-level audio inputs; Maximum Input Level: 7.75 Vrms, +20 dBu; Input Impedance: 20k Ohms
<b>ALS OUT</b>	(1) 3.5 mm connector, female; Unbalanced line level audio output, 0.316 Vrms, -10 dBV nominal; Maximum Output Level: 2.24 Vrms, +7 dBV (+9.2 dBu); Fixed audio output for assisted listening devices duplicates the summed (Unbalanced + Balanced) audio inputs
<b>REMOTE</b>	(1) 2 pin 3.5 mm detachable terminal block; Connect to dry contact closure to place amplifier in standby mode.
<b>G</b>	(1) 6-32 screw; Chassis ground lug
<b>100-240V~ 370-200 mA 50/60 Hz</b>	(1) IEC 60320 C14 main power inlet; Mates with removable power cord, included

#### Controls & Indicators

<b>PWR</b>	(1) White/Red LED; White indicates amplifier is on and ready for use; Red indicates amplifier is in standby
<b>HI-Z</b>	(1) White LED; Indicates when Hi-Z mode is enabled (70V or 100V); Channels 1 - 2 are bridged and set to 70V or 100V operation
<b>SIGNAL</b>	(2) White/Red LEDs (one per input); White indicates when an active input signal is present Red indicates when an active input signal clip/limiting is present
<b>FAULT</b>	(2) Red LEDs (one per input); Indicates that the input channel is faulted
<b>GAIN 1-2</b>	(2) Screwdriver-adjustable, detented rotary controls, one per input channel; Adjusts the input attenuation level for the corresponding amplifier channel

# AMP-X75

## X-Series Amplifier, 75 W

### Modes

(1) Slide switch;  
Selects stereo, summed, bridged, 70V, or 100V operation

- **STEREO (LoZ):** The input signal received on each channel is sent to its respective output for use in applications where left and right channel separation is required. The two GAIN controls are independently adjustable.
- **SUM (LoZ):** The input signals sent to a channel pair (1 + 2) are summed and sent to their respective individual outputs. The two GAIN controls are independently adjustable.
- **BRIDGE (LoZ):** The input signals sent to a channel pair (1 + 2) are summed and sent to a bridged output (1 + 2) for use in high-power applications. The GAIN 1 control adjusts the bridged 1 + 2 output.
- **70V (Hi-Z):** The input signals sent to a channel pair (1 + 2) are summed and sent to a bridged output (1 + 2) for use in Hi-Z 70V applications. The GAIN 1 control adjusts the bridged 1 + 2 output.
- **100V (Hi-Z):** The input signals sent to a channel pair (1 + 2) are summed and sent to a bridged output (1 + 2) for use in Hi-Z 100V applications. The GAIN 1 control adjusts the bridged 1 + 2 output.

### Power

<b>Main Power</b>	370-200 mA @ 100-240VAC, 50/60 Hz
<b>Power Consumption</b>	18.63 W, (2 channels driven at 1/8th output power, 4 ohms); 7.60 W, idle (Hi-Z mode); 0.41 W, standby (230VAC/50 Hz)

### Environmental

<b>Temperature</b>	41 to 104°F (5° to 40°C)
<b>Humidity</b>	10% to 90% RH (non-condensing)
<b>Heat Dissipation</b>	63.6 BTU/hr @ 4 Ohms, all channels driven at 1/8th output power; 25.9 BTU/hr, idle (Hi-Z mode); 1.4 BTU/hr in standby

### Construction

<b>Chassis</b>	Metal, convection cooled (fan less)
<b>Front Panel</b>	Metal, black finish with polycarbonate label overlay
<b>Mounting</b>	Freestanding, surface mount, or 1/4 width 1 RU 19 in. rack mountable; Gangable with other Crestron modular AMP series products (adhesive feet, surface mounting, rack mounting, and ganging hardware all included)

### Dimensions

<b>Height</b>	1.75 in. (44 mm) without feet; 1.83 in. (46 mm) with feet
<b>Width</b>	4.33 in. (110 mm) without mounting brackets; 19.00 in. (483 mm) with mounting brackets
<b>Depth</b>	8.78 in. (223 mm)

### Weight

2.1 lb (0.95 kg)

### Compliance

**Regulatory Model: M201929003**

ENERGY STAR, ErP (1275/2008/EC), Intertek® Listed for US & Canada, FCC Class B residential use

### Model

**AMP-X75**  
X-Series Amplifier

# AMP-X75

## X-Series Amplifier, 75 W

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Intertek is either a trademark or registered trademark of Intertek Group in the United States and/or other countries. ENERGY STAR is either a trademark or a registered trademark of the United States Environmental Protection Agency in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2024 Crestron Electronics, Inc.

Rev 04/11/24

# AMP-X75

## X-Series Amplifier, 75 W

