

## 2-Channel DigitalMedia™ Fiber Output Card for DM® Switchers

- > Modular output card for a DM-MD8X8, DM-MD16X16, or DM-MD32X32 switcher
- > Provides two independent DM® Fiber outputs
- > Supports cable lengths up to 1000 ft (300 m) using CresFiber® 8G or OM2/OM3 duplex multimode fiber<sup>[1]</sup>
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Occupies a single output card slot

The DMC-FO is an output card designed for use with any card-based Crestron® DigitalMedia™ Switcher. It provides two independent DM® Fiber outputs. Each DM Fiber output enables connection to a DM Fiber Receiver, or the input of another DM switcher, using two strands of multimode fiber. Both outputs are capable of handling video resolutions up to Full HD 1080p, as well as computer resolutions up to UXGA and WUXGA. DM Fiber transports uncompressed high-definition video and computer signals over distances up to 1000 feet (300 m) using CresFiber® 8G or third-party OM2/OM3 duplex multimode fiber optic cable.<sup>[1]</sup>

Are you upgrading an existing DM switcher that has older “multi-gang” DMCO-series output cards? Use the online [Output Card Additions and Upgrades Tool](#) to update your existing output cards and switcher to the new “single-gang” output card format.

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.


### SPECIFICATIONS

#### Video

**Signal Type:** DM® Fiber (DigitalMedia™ over two multimode fiber optic strands)

**Formats:** DM Fiber with Deep Color & 3D; HDCP content protection support)

**Resolutions, Progressive:** 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock



**Resolutions, Interlaced:** 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

#### Audio

**Signal Type:** DM Fiber

**Formats:** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

#### Communications

**DigitalMedia:** DM Fiber, HDCP, EDID, CEC, Ethernet

#### Connectors

**D, M:** (4) SC female optical fiber connectors comprising (2) DM Fiber outputs;

Each DM Fiber output connects to the DM Fiber input of a DM receiver or other DM device via CresFiber® 8G fiber optic cable<sup>[1]</sup>

#### Construction

Plug-in card, occupies (1) DM switcher output card slot, includes metal faceplate w/black finish

#### Weight

6.2 oz (176 g)

# DMC-F0 2-Channel DigitalMedia™ Fiber Output Card for DM® Switchers

## MODELS & ACCESSORIES

### Available Models

**DMC-F0:** 2-Channel DigitalMedia™ Fiber Output Card for DM® Switchers

### Available Accessories

**CRESFIBER8G-NP:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

**CRESFIBER8G-P:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

**CRESFIBER-CONN-SC50UM-12:** CresFiber® Fiber Optic Cable Connector (AFL Telecommunications®), SC 50µm, 12-Pack

**CRESFIBER-TK:** CresFiber® Termination Kit (AFL Telecommunications®)

**CRESFIBER-DUAL-SC-P:** CresFiber® Duplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

**CRESFIBER-DUAL-SC-ARMORED-P:** CresFiber® ARMORED Duplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum

**CRESFIBER-SINGLE-SC-CLEAR-NP:** CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum

**MP-WP Series:** Media Presentation Wall Plates

### Notes:

1. The maximum cable length for DigitalMedia Fiber (DM Fiber) is 1000 ft (300 m) using [CRESFIBER8G](#), [CRESFIBER-DUAL-SC](#), or third-party OM2/OM3 duplex multimode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, CresFiber, DigitalMedia, and DM are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.

©2015 Crestron Electronics, Inc.