

DIN-EN-2X18-HC-2OPEN

DIN Rail Enclosure with 2 DIN Rails and 2 Cover Openings

- *DIN rail enclosure for the DIN-THSTAT thermostat and other DIN modules (sold separately)*
- *2 Cover openings provide access for up to 4 DIN modules (9M wide) through the cover*
- *2 DIN rails, 18M wide*
- *Raised DIN rails allow for additional wiring behind the DIN rails*
- *Elegantly finished black cover*
- *Blank cover plates (3M and 9M wide) supplied to cover unpopulated cover openings*
- *Hinged cover for easy access to the equipment wiring*
- *UL® Listed*

The Crestron® DIN-EN-2X18-HC-2OPEN is a UL® Listed enclosure that provides an attractive centralized mounting solution for the DIN-THSTAT thermostats and other DIN rail modules. An elegantly finished black cover matches the aesthetic of the DIN-THSTAT thermostat and provides a professional look and feel. A hinged cover provides easy access to equipment wiring while openings in the cover provide access to the DIN modules through the cover.

DIN Rail Mounting

The DIN-EN-2X18-HC-2OPEN enclosure utilizes 18M wide DIN rails to install up to 2 DIN modules (9M wide) per DIN rail.

Raised DIN rails allow access to the DIN module's control surface through the cover openings. The DIN-EN-2X18-HC-2OPEN provides 2 raised DIN rails (18M wide) with the ability to install 4 DIN modules (9M wide).

Specifications

DIN Rail Detail

- (2) DIN rails, 18M wide (342 mm x 35 mm);
- (2) Raised DIN rails to allow access to the DIN module through the (2) cover openings

Cover Openings

- (2) Cover openings;
- Allows access to DIN modules through the cover opening; Class 2 terminations are allowed in this area

NOTE: The DIN-EN-2X18-HC-2OPEN does not contain a fire enclosure.

Environmental

Temperature 32° to 104° F (0° to 40° C)

Humidity 10% to 90% RH (noncondensing)

Construction

Enclosure 16-gauge galvanized steel

Cover 16-gauge galvanized steel;
Black powder coat finish;
Cover openings for DIN module access;
Hinged, secure with included screws

Mounting Surface or flush wall mount

NOTE: Custom framing may be required to flush mount.

Dimensions

Height 12.32 in (323 mm)

Width 14.13 in (359 mm)

Depth 4.38 in (111 mm)

View the DIN-EN-2X18-HC-2OPEN CAD drawing for detailed dimension information.

Weight

10.75 lb (4.9 kg)

Compliance

UL Listed

DIN-EN-2X18-HC-2OPEN

DIN Rail Enclosure with 2 DIN Rails and 2 Cover Openings

Models

DIN-EN-2X18-HC-2OPEN

DIN Rail Enclosure with 2 DIN Rails and 2 Cover Openings

DIN-EN-3X18-HC-2OPEN

DIN Rail Enclosure with 3 DIN Rails and 2 Cover Openings

DIN-EN-6X18-HC-5OPEN

DIN Rail Enclosure with 6 DIN Rails and 5 Cover Openings

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2019 Crestron Electronics, Inc.

Rev 10/03/19