ULTIMATE IC3-AW-SA-TWEETER-EACH

Ultimate 3 in. All Weather In-Ceiling Tweeter, Single



- 2 in. (51 mm) wideband ceramic coated aluminum tweeter
- IP66 rated for dust and water with weatherized construction
- 75 W (RMS), 200 W (Peak) power handling
- 200 Hz to 20 kHz (±3 dB) frequency response
- 8 Ohms nominal impedance

The Crestron Ultimate in-ceiling tweeter made by Origin Acoustics delivers the pinnacle of performance for demanding residential installations.

The <u>ULTIMATE IC3-AW-SA-TWEETER-EACH</u> resembles 3.5 in. (89 mm) designer lighting, blending seamlessly into the ceiling alongside a <u>LFX-DL-TUNC</u> for a sophisticated, uniform appearance. Weatherized construction allows for use in a shower, sauna, locker room, yacht, and marine applications.

The ULTIMATE IC3-AW-SA-TWEETER-EACH is part of the ULTIMATE IC3-SA-WOOFER/TWEETER-W-T-KIT that includes <u>ULTIMATE-IC3-AW-SA-BOX-WOOFER-W-T-EACH</u> as well.

In the pre-construction phase, just the ULTIMATE-IC3-AW-SA-BOX-WOOFER-W-T-EACH can be installed, and once construction is finished, the ULTIMATE IC3-AW-SA-TWEETER-EACH can be installed to complete the speaker setup.

Specifications

ULTIMATE IC3-AW-SA-TWEETER-EACH

Tweeter 2 in. (51 mm) wide band ceramic coated

aluminum cone

Neodymium transducer

Crossover 200 Hz

Point

Impedance 8 Ohms nominal

Frequency 200 Hz to 20 kHz (±3 dB)

Response

Program: 102 dB;

Maximum Program: 102 dB;
SPL Peak: 107 dB

Coverage 100° conical

Sensitivity 82 dB @ 1 W/1 M

Input 2-pin pluggable screw terminals

Max Wire 12 AWG (4 mm²)

Size

Enclosure Cast Aluminum

Material

Splash IP66 rated for water

Resistance

 Height
 5.57 in. (141 mm)

 Diameter
 2.85 in. (72 mm)

 Weight
 0.55 lb (0.24 kg)

Environmental

Temperature 4° to 176°F (-15.5° to 80°C)

Humidity 10% to 95% RH (non-condensing)

Compliance

Regulatory Model: M202145001

CE, Intertek® Listed for US & Canada, FCC Part 15 Class B digital device

To search for product certificates, refer to support.crestron.com/app/certificates.

Model

ULTIMATE IC3-AW-SA-TWEETER-EACH

Ultimate 3 in. All Weather In-Ceiling Tweeter, Single



ULTIMATE IC3-AW-SA-TWEETER-EACH

Ultimate 3 in. All Weather In-Ceiling Tweeter, Single

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at www.crestron.com/warranty.

The specific patents that cover Crestron products are listed online at ${\it www.crestron.com/legal/patents}.$

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Intertek is either a trademark or registered trademark of Intertek Group in the United States and/or other countries. Origin Acoustics is either a trademark or a registered trademark of Origin Acoustics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2023 Crestron Electronics, Inc.

Rev 05/18/23



ULTIMATE IC3-AW-SA-TWEETER-EACH

Ultimate 3 in. All Weather In-Ceiling Tweeter, Single

ULTIMATE IC3-AW-SA-TWEETER-EACH





