

Vivotek	FE8172		
Description	Fisheye camera.		
Number of documented streams:	3	Documented Simultaneous Streams:	10

TSX

MJPEG

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	2~3 seconds
URL with user name and password: http://<IP address>:<port>/video.mjpg?user=<username>&pw=<password>			
URL without username and password N/A			
URL Example http://192.168.1.115:80/video.mjpg?user=admin&pw=admin			

H.264

Supported	Yes		
Resolution:	720x1280	Max Bandwidth	2 Mb/s
Frames per second (fps):	15	Switching Time	1 ~ 2 seconds
I-Frame Setting	1/S		
URL with user name password: rtsp://<username>:<password>@<IP address>:<port>/live.sdp			
URL without user name password: rtsp://<IP address>:<port>/live.sdp			
URL Multicast: -			
URL Example rtsp://admin:admin@192.168.1.112:554/live.sdp			

TPMC-V12/15, DGE-2. TPMC-8X-GA**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Good
Frames per second (fps):	15	Switching Time:	1-2 secs
URL with user name and password:			
http://[<username>:<password>@]<IP address>:<port>/<[video.mjpeg video2.mjpg video3.mjpg]>			
URL without username and password			
N/A			
URL Example			
http://admin.admin@172.30.176.163:80/video.mjpg			

H.264

Supported	Yes		
Resolution:	1280x720	Max Bandwidth	Avg Targer bit rate 3M
Frames per second (fps):	5	Switching Time	1-4 secs (depends on configuration)
I-Frame Setting	1/4 S		
URL with user name password:			
rtsp://[<username>:<password>@]<IP address>:<port>/<[live.sdp live2.sdp live3.sdp]>			
URL without user name password:			
rtsp://<IP address>:554/live.sdp			
URL Multicast:			
Yes			
URL Example			
rtsp://admin.admin@172.30.177.85:554/live.sdp			

TPMC-4SM**MJPEG**

Supported:	Yes		
Resolution:	384x216	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	2 ~ 6 seconds
URL with user name and password:			
<input type="checkbox"/> <a href="http://<username>:<password>@<IP address>:<port>/video.mjpg">http://<username>:<password>@<IP address>:<port>/video.mjpg			
URL without username and password			
-			
URL Example			
-			

H.264

Supported	Slow Switching		
Resolution:	384x216	Max Bandwidth	128Kbps
Frames per second (fps):	15	Switching Time	6 ~ 7 seconds
I-Frame Setting	1/S		
URL with user name password:			
<input type="checkbox"/> <a href="rtsp://<username>:<password>@<IP address>:<port>/live.sdp">rtsp://<username>:<password>@<IP address>:<port>/live.sdp			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			

Crestron App**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Standard
Frames per second (fps):	5	Switching Time:	2-4sec
URL with user name and password:			
http://<Ipaddress>:<Port>/video.mjpg?user=admin&pw=admin			
URL without username and password			
N/A			
URL Example			
http://172.30.177.85:554/video.mjpg?user=admin&pw=admin			

H.264

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
N/A			
URL Multicast:			
N/A			
URL Example			
N/A			